



CARBON DIOXIDE HAND PORTABLE AND WHEELED EXTINGUISHERS

SIZES 5 LB. (2.3 KG) TO
100 LB. (45.4 KG)

FEATURES

- UL Listed
- Simple, trouble-free operation and maintenance
- Features upright positive on-off operation utilizing squeeze-grip activation
- Non-corrosive, non-conductive, clean extinguishing agent leaves no residue
- Strong, impact-resistant discharge horn
- One person operation
- Suitable for use in temperatures from -40 °F to 120 °F (-40 °C to 49 °C)
- Six-year limited warranty



006981

PART NO.	MODEL	UL RATING	EFFECTIVE RANGE	CAPACITY	DISCHARGE TIME	DIAMETER	WIDTH	HEIGHT
552083	CO2-050-I	5-B:C	5-6 ft. (1.5-1.8 m)	5 lbs. (2.3 kg)	10-12 seconds	5.3 in. (13.5 cm)	10 in. (25.4 cm)	18.9 in. (48.0 cm)
552084	CO2-10-I	10-B:C	5-6 ft. (1.5-1.8 m)	10 lbs. (4.5 kg)	10-12 seconds	6.9 in. (17.5 cm)	12.5 in. (31.8 cm)	21.3 in. (54.1 cm)
552085	CO2-15-I	10-B:C	7-10 ft. (2.1-3.0 m)	15 lbs. (6.8 kg)	13-15 seconds	6.9 in. (17.5 cm)	12.5 in. (31.8 cm)	27.9 in. (70.9 cm)
552086	CO2-20-I	10-B:C	7-10 ft. (2.1-3.0 m)	20 lbs. (9.1 kg)	15-17 seconds	8 in. (20.3 cm)	13.5 in. (34.3 cm)	28 in. (71.1 cm)
551883	CO2-50	20-B:C	10-16 ft. (3.0-4.9 m)	50 lbs. (22.7 kg)	35 seconds	26 in. (66.0 cm)	22 in. (55.9 cm)	52 in. (132.1 cm)
551884	CO2-100	20-B:C	10-16 ft. (3.0-4.9 m)	100 lbs. (45.4 kg)	70 seconds	30 in. (76.2 cm)	22 in. (55.9 cm)	52 in. (132.1 cm)
552091	CO2-050-I UL S/E	5-B:C	5-6 ft. (1.5-1.8 m)	5 lbs. (2.3 kg)	10-12 seconds	5.3 in. (13.5 cm)	10 in. (25.4 cm)	18.9 in. (48.0 cm)
552092	CO2-10-I UL S/E	10-B:C	5-6 ft. (1.5-1.8 m)	10 lbs. (4.5 kg)	10-12 seconds	6.9 in. (17.5 cm)	12.5 in. (31.8 cm)	21.3 in. (54.1 cm)
552093	CO2-15-I UL S/E	10-B:C	7-10 ft. (2.1-3.0 m)	15 lbs. (6.8 kg)	13-15 seconds	6.9 in. (17.5 cm)	12.5 in. (31.8 cm)	27.9 in. (70.9 cm)
552094	CO2-20-I UL S/E	10-B:C	7-10 ft. (2.1-3.0 m)	20 lbs. (9.1 kg)	15-17 seconds	8 in. (20.3 cm)	13.5 in. (34.3 cm)	28 in. (71.1 cm)

Underwriters Laboratories Inc. Listed and U.S.C.G. Approved

CLASS **B** **C** FIRES



TYCO SAFETY PRODUCTS
One Stanton Street
Marinette, WI 54143 USA

Phone: 800-526-1079 or 715-732-3465
FAX: 877-329-7976 or 715-732-3569
www.pyrochem.com